


## Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

|                        |              |
|------------------------|--------------|
| <b>Creation Date:</b>  | 05/09/2018   |
| <b>Datasheet No:</b>   |              |
| <b>Parker Part No:</b> | 933263Q      |
| <b>OEM:</b>            | Pall         |
| <b>OEM Part No:</b>    | HC9400FKP39Z |

### Product Dimensions

|               |       |               |       |
|---------------|-------|---------------|-------|
| <b>A (mm)</b> | 96.5  | <b>(inch)</b> | 3.80  |
| <b>B (mm)</b> | 56.1  | <b>(inch)</b> | 2.21  |
| <b>C (mm)</b> | 56.1  | <b>(inch)</b> | 2.21  |
| <b>D (mm)</b> | 96.5  | <b>(inch)</b> | 3.80  |
| <b>E (mm)</b> | 988.1 | <b>(inch)</b> | 38.90 |



### Construction Materials

|                                |  |
|--------------------------------|--|
| <b>Seal(s):</b>                | FKM: Fluorocarbon  |
| <b>Top Endcap:</b>             | Glass reinforced nylon                                     |
| <b>Bottom Endcap:</b>          | Glass reinforced nylon                                     |
| <b>Inner Support Cylinder:</b> | Steel zinc plated  |
| <b>Filter Media:</b>           | Multilayer fiberglass with epoxy coated mesh on both sides |

### Calculated Performance Criteria

|   |   |
|---|---|
| <b>Differential Pressure (<math>\Delta p</math>):</b> | bar @ l/min   |
| <b>Tested to ISO3968 @ 32 cSt</b>                     | psi @ gpm   |
| <b>Efficiency</b>                                     | >Beta 200 @ 4 microns & greater<br>>Beta 1000 @ 5 microns & greater |
| <b>Minimum Collapse Pressure:</b>                     | >21 bar   |
| <b>Tested to ISO2941</b>                              | >300 psi  |
| <b>Dirt Holding Capacity acc. to ISO16889</b>         |   |